
## **MORE EFFICIENCY FOR THE LED WORLD**



LED line PRIME

## LINKER TRI-PROOF 21W 4000K 3150lm 150lm/W IP65 60cm Emergency module 3H AT PRIME





#### EAN: 5905378212244

â D

LINKER 21W from LED line PRIME is a modern lighting solution, providing exceptional light performance of 150 lm/W and a total light stream of 3150 lumens. Its colour of light 4000K guarantees natural color reproduction, which favors visual comfort. IP65 leak class and IK08 resistance ensure reliable operation in difficult weather conditions.





#### Technical data

Parameter	Value
Operating time in emergency mode	3 h
Emergency module test	Autotest
ULOR	3 %
Voltage	• 220-240 V AC
Luminous efficacy	150
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	3150
Colour consistency in McAdam ellipses	≤6
Warranty (years)	5
Dimmable function	PWM
Survival factor	0.9
Lifetime L70B50	100 000 h
Frequency of the supply voltage	50/60Hz

Parameter	Value	
Colour rendering index Ra	80	
Colour Grey		
The lumen maintenance factor	96	
Beam angle	120	
Material (cover)	polycarbonate	
Material (housing)	Polycarbonate	
Lifespan	100 000 h	
Number of on/off cycles	50000	
Colour consistency in McAdam ellipses	≤6	
Ambient temperature suitable for operation	`-25 ÷ 45	
IEC protection class	II	
Lamp's warm-up time to 60%	ls	
Correlated colour temperature	• 4000 K	
Power	• 21 W	

# **MORE EFFICIENCY FOR THE LED WORLD**



### LED line PRIME


Code: 479587-AW3HAT

#### EAN: 5905378212244

## LINKER TRI-PROOF 21W 4000K 3150lm 150lm/W IP65 60cm Emergency module 3H AT PRIME


echnical drawing Light d		Light distribution	ht distribution	
Additional product photos				
1 Mar 10				


### Logistics data



Single packaging

**Bulk packaging** 





Europallet

# **MORE EFFICIENCY FOR THE LED WORLD**



LED line PRIME

Code: 479587-AW3HAT

EAN: 5905378212244

LINKER TRI-PROOF 21W 4000K 3150lm 150lm/W IP65 60cm Emergency module 3H AT PRIME

Example application