

LED line

Code: 249143

EAN: 5901583249143

LED line strip 600 SMD 12V 4000K 9,6W



product_card.label_technical_data

Parameter	Value	Parameter	Value
Luminous efficacy	77 lm/W	Compatible dimmer type	PWM
Colour of the light	White	Laminate (colour)	White
Energy efficiency class 2019/2015	G	Laminate (thickness)	2
Colour consistency in McAdam ellipses	≤3	LED quantity (lm)	120
IP protection rating	IP20	Cutting section	2,5
Warranty (years)	5	Type of adhesive tape	3M 300 LSE
Dimmable function	PWM	Lifespan	100000
Survival factor	0.9	Number of on/off cycles	50000
Minimum purchase quantity	5	Colour consistency in McAdam ellipses	≤3
Lifetime L70B50	50 000	Ambient temperature suitable for operation	-20÷45 °C
Wattage (lm)	9,6 W	For indoor use	Inside
Luminous flux (lm)	680lm	IEC protection class	III
Current (lm)	0,8	Full box quantity	75 pc
Colour rendering index Ra	90	Lamp's warm-up time to 60%	1
CRI colour rendering index	90	Width	8 mm
Metres per roll	5	Height	2,5 mm
The lumen maintenance factor	96 %	Energy class	A
Beam angle	120 °	Power	• 9.6
LED type	SMD2216	Voltage	• 12 V DC
Not dimmable	TAK	Correlated colour temperature	• 4000 K

LED line


Code: 249143

EAN: 5901583249143

LED line strip 600 SMD 12V 4000K 9,6W

product_card.label_dimensions


product_card.label_curve_light



product_card.label_product_gallery




product_card.label_logistic_data




Single packaging

1



Bulk packaging

Number of pieces/tape in meters pack zb	100
Width	340 mm
Height of collective packaging	280
Length	440 mm
Weight	0,11 kg
Volume	0,042 m3



Europallet

Number of pieces/tapes in meters euro pallet	1800
Quantity collective euro pallet	24
Weight of a euro pallet	2,64 kg
Pallet height	984
Quantity in 1 layer	8
Number of layers	3

LED line

Code: 249143

EAN: 5901583249143

LED line strip 600 SMD 12V 4000K 9,6W

Example application