

LED line LITE

Code: 203938-AW3HAT

EAN: 5905378216686

Panel Backlit 2in1 40W 4000K 4000LM
60x60 black emergency module 3h
autotest LITE



The 40W black Backlit 2in1 panel is a modern lighting solution for excellent performance. It emits a light stream of 4,000 lumens, at 4000K light colour temperature, which guarantees neutral, natural light. The panel has a high light efficiency of 100 lm/W and a light stream conservation factor of 96.



Technical data

Parameter	Value
Operating time in emergency mode	3 h
Emergency module test	autotest
Voltage	<div><ul style="list-style-type: none">220-240 V AC</div>
Luminous efficacy	100
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	4000
Colour consistency in McAdam ellipses	≤6
Warranty (years)	2
IP protection rating	IP20
Dimmable function	PWM
Survival factor	0.9
Lifetime L70B50	30 000 h
Frequency of the supply voltage	50/60Hz

Parameter	Value
Colour rendering index Ra	80
The lumen maintenance factor	96
Beam angle	120
Material (cover)	polystyrene
Material (housing)	Metal
Power Factor	0,9
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
IEC protection class	I
IK protection rating	02
Lamp's warm-up time to 60%	1 s
Correlated colour temperature	<div><ul style="list-style-type: none">4000 K</div>
Power	<div><ul style="list-style-type: none">40 W</div>

LED line LITE

Code: 203938-AW3HAT

EAN: 5905378216686

**Panel Backlit 2in1 40W 4000K 4000LM
60x60 black emergency module 3h
autotest LITE**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line LITE

Code: 203938-AW3HAT

EAN: 5905378216686

**Panel Backlit 2in1 40W 4000K 4000LM
60x60 black emergency module 3h
autotest LITE**

Example application