

LED line PRIME

Code: 210967

EAN: 5905378210967

LED line strip 600 SMD 12V 2700K 9,6W

ATG

F

New



Technical data

Parameter	Value	Parameter	Value
Luminous efficacy	100 lm/W	LED type	SMD 2835
Colour of the light	White	LED quantity	600
Energy efficiency class 2019/2015	F	Compatible dimmer type	PWM
Colour consistency in MacAdam ellipses	≤3	Laminate (colour)	White
IP protection rating	IP20	Laminate (thickness)	2
Warranty (years)	5	LED quantity (lm)	120
Dimmable function	PWM	Cutting section	2,5
Survival factor	0.9	Type of adhesive tape	3M 300 LSE
Minimum purchase quantity	5	Colour consistency in MacAdam ellipses	≤3
Lifetime L70B50	30 000	Ambient temperature suitable for operation	-25÷45 °C
Wire length	200 mm	For indoor use	Inside
Wattage (lm)	9,6 W	IEC protection class	III
Luminous flux (lm)	960	Length	5000 mm
Current (lm)	0,8	Height	2,5 mm
Colour rendering index Ra	80	Power	• 9,6
Metres per roll	5	Voltage	• 12 V DC
The lumen maintenance factor	96 %	Correlated colour temperature	• 2700 K
Beam angle	120 °		

LED line PRIME


Code: 210967

EAN: 5905378210967

LED line strip 600 SMD 12V 2700K 9,6W

Dimensions


Light distribution



Additional product photos




Logistics data




Single packaging

Width	153 mm
Height	15 mm mm
Length	153 mm mm
Weight	0,13 kg kg



Bulk packaging

Number of pieces/tape in meters pack zb	40 szt.
Width	360 mm mm
Height of collective packaging	180 mm
Length	320 mm mm
Weight	5,1 kg kg
Volume	0,020 m3 m3



Europallet

Number of pieces/tapes in meters euro pallet	12000 m
Quantity collective euro pallet	2400 szt.
Weight of a euro pallet	331,0 kg
Pallet height	1800 mm
Quantity in 1 layer	240 szt.
Number of layers	10

LED line PRIME

Code: 210967

EAN: 5905378210967

LED line strip 600 SMD 12V 2700K 9,6W

Example application