

LED line LITE

Code: 245961

EAN: 5901583245961

**LED bulb G9 6000K 6W 550lm 230V
270° Ceramic LITE**



LITE G9 6W 6000K LED line bulb is an advanced light source that emits a cool, white light with a temperature of 6000 K. It is characterized by a light stream of 550 lm and high energy efficiency of 92 lm/W. Thanks to the ceramic housing, it provides a durability of up to 30,000 hours, and its universal G9 handle facilitates installation in standard frames.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 6 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 6000 K
Colour of the light	White
Colour rendering index Ra	80
Luminous efficacy	92
Luminous flux	550 lm
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Beam angle	270 °
LED type	SMD2835
Power Factor	0,5
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	61
Fixture's diameter	16 mm
Colour	white
Material (housing)	Ceramics

LED line LITE

Code: 245961


EAN: 5901583245961

**LED bulb G9 6000K 6W 550lm 230V
270° Ceramic LITE**

Technical drawing






Light distribution



Additional product photos

Logistics data



Single packaging

Quantity	1
Width	50 mm
Height	50 mm
Length	60 mm
Weight	0,02 kg

Bulk packaging

Quantity	500
Width	610 mm
Height	235 mm
Length	150 mm
Volume	0,021 m ³
Weight	10,06 kg
Comments	

Europallet

Quantity	25000
Height	1880 mm
Quantity in layer	4000
Number of layers	8
Bulk quantity	32000
Weight	643,84 kg

LED line LITE

Code: 245961

EAN: 5901583245961

**LED bulb G9 6000K 6W 550lm 230V
270° Ceramic LITE**

Example application