


LED line PRIME Ceiling lamp ACTON 18W 2000lm 4000K IP54 round



The simplicity of installation and high performance are only selected features thanks to which the ACTON ceiling lamp can add a new dimension to the lighting of many spaces. Thanks to the separation of the glowing part of the ceiling from the base, the lamps are easy to mount on the wall and ceiling. The light efficiency of 105-111lm/W, which distinguishes the fixtures in the segment of other ceiling lamps available on the market, is also noteworthy.

Versatility and universality

The fixture gives the possibility of comfortable lighting both inside and outside buildings.

- Thanks to the power from 18 W to 24 W, it provides a wide range of lighting possibilities.
- The ACTON ceiling lamp is offered in two casing variants - round and square, allowing the choice of shape depending on individual preferences.
- The fixtures are also available in two color temperature versions 4000K (18W and 24W) and 3000K (18W).
- The ceiling lamp can be equipped with a microwave motion and dusk sensor with a 360-degree range within 8 meters, providing additional safety.

Durable and aesthetic design

Simple and quick installation and maximum durability are other features that distinguish ACTON ceilings.

- The casing and shade are made of impact-resistant polycarbonate, which allows for safe operation outdoors (IP54) and provides excellent protection against mechanical damage (IK08).
- Thanks to the well-thought-out project, the ceilings are not only durable, but also aesthetic - they are characterized by a simple and elegant design, which makes them perfectly match various styles of arrangements.
- A high color rendering index (Ra>80) ensures natural lighting, which is scattered by the milky shade, creating a pleasant visual effect.

Opt for ACTON ceilings, which will not only illuminate your spaces but also add elegance and functionality to them. Take advantage of our offer and enjoy high-quality lighting for many years.



Yellow free technology means that the housing of this product is made of high quality material which is resistant to yellowing degeneration caused by UV radiation, thanks to which the product maintains its aesthetic appearance for many years.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Manufacturer issues a 5-year warranty for this product.



Beam angle



Voltage range and voltage type



Ambient temperature suitable for operation



LED type



Lifespan

| Parameter | Value |
|-----------------------------------|----------|
| Luminous efficacy | 110 lm/W |
| Power | 18 W |
| Colour of the light | White |
| Energy efficiency class 2019/2015 | F |
| Luminous flux | 2000 lm |
| Correlated colour temperature | 4000 K |

| Parameter | Value |
|------------------------------|---------------|
| Colour | White |
| The lumen maintenance factor | 96 % |
| Fixture's diameter | 220 |
| Beam angle | 120 ° |
| Material (cover) | polycarbonate |
| Material (housing) | Polycarbonate |

| | |
|---------------------------------------|-------------|
| Colour consistency in McAdam ellipses | ≤6 |
| IP protection rating | 54 |
| Warranty (years) | 5 |
| Dimmable function | PWM |
| Survival factor | 0.9 |
| Lifetime L70B50 | 30 000 |
| Weight | 500 g |
| Supply voltage range and voltage type | 220-240 VAC |
| Frequency of the supply voltage | 50/60Hz |
| Colour rendering index Ra | 80 |

| | |
|--|-----------|
| LED type | SMD2835 |
| Power Factor | 0,9 |
| Colour consistency in McAdam ellipses | ≤6 |
| Ambient temperature suitable for operation | -25÷40 °C |
| For indoor and outdoor use | YES |
| IEC protection class | II |
| IK protection rating | 08 |
| Lamp's warm-up time to 60% | 1 |
| Height | 51 mm |

Single packaging



| | |
|--------|--------|
| Width | 220 mm |
| Height | 220 mm |
| Length | 60 mm |
| Weight | 0,6 kg |

Bulk packaging



| | |
|---|----------------------|
| Number of pieces/tape in meters pack zb | 20 szt. |
| Width | 615 mm |
| Height of collective packaging | 250 mm |
| Length | 470 mm |
| Weight | 12,35 kg |
| Volume | 0,072 m ³ |

Europallet



| | |
|--|----------|
| Number of pieces/tapes in meters euro pallet | 400 |
| Quantity collective euro pallet | 280 szt. |
| Weight of a euro pallet | 172,9 kg |
| Pallet height | 1750 mm |
| Quantity in 1 layer | 40 szt. |
| Number of layers | 7 |