



# LED line® strip 300 SMD 12V red 4,8W IP67



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



Yellow free technology means that the housing of this product is made of high quality material which is resistant to yellowing degeneration caused by UV radiation, thanks to which the product maintains its esthetic appearance for many years.



This product is featured by a high degree of IP protection, which makes it suitable for a broader range of lighting applications and offers high safety of use.



Manufacturer issues a 3-year warranty for this product.



Beam angle



Voltage range and voltage type



Ambient temperature suitable for operation



LED type



Lifespan



LED quantity (1m)




Dimmable


Parameter	Value
Colour of the light	Red
IP protection rating	67
Warranty (years)	3
Dimmable function	PWM
Minimum purchase quantity	5
Lifetime L70B50	30 000
Wattage (1m)	4,8 W
Current (1m)	0,4
Supply voltage range and voltage type	12 VDC
Metres per roll	5
The lumen maintenance factor	>0,7 %
Beam angle	120 °
LED type	SMD3528
Not dimmable	TAK
Compatible dimmer type	PWM
Laminate (colour)	White

Parameter	Value
Laminate (thickness)	2
LED quantity (1m)	60
Cutting section	5
Type of adhesive tape	Piankowa
Lifespan	100000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤3
Ambient temperature suitable for operation	-20÷45 °C
For indoor and outdoor use	YES
IEC protection class	III
Full box quantity	40 pc
Lamp's warm-up time to 60%	1
Width	10 mm
Height	5 mm
Product weight with packaging	301 g
Master carton weight (kg)	12,04

Single packaging




Bulk packaging



100

Europallet



24  
984  
8  
3