

LED line PRIME LED BULB MR11 3W 4000K 330lm 10-14V AC/DC 38°



Manufacturer issues a 5-year warranty for this product.



Voltage range and voltage type



Lamp type



Lifespan



The structural design of this product ensures effective heat dissipation.



Beam angle



LED type



Parameter	Value
Luminous efficacy	110 lm/W
Power	3 W
Colour of the light	White
Energy efficiency class 2019/2015	F
Luminous flux	330 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	20
Warranty (years)	5
Dimmable function	No
Survival factor	0.9
Lifetime L70B50	30 000
Supply voltage range and voltage type	10-14V AC/DC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White
The lumen maintenance factor	96
Lamp's type	MR11
Lamp's diameter	35
Beam angle	38 °
Material (housing)	Ceramic
LED type	SMD2835

Parameter	Value
Lifespan	30000
Power Factor	0,5
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
For indoor use	Inside
Full box quantity	100 pc
Lamp's warm-up time to 60%	1
Height	35 mm
Master carton weight (kg)	4
EPREL ID	632 084
Angle for useful luminous flux (EPREL)	Narrow cone of 90 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	DLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	NMLS
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
R9 colour rendering index value (EPREL)	13
Total luminous flux (EPREL)	330
On-mode power Pon (EPREL)	3
Useful luminous flux Φuse (EPREL)	260

Single packaging



20
62
20
1

Bulk packaging



100

Europallet



5