

**LED line® G9 12W 3000K 1160lm 220-240V**

Manufacturer issues a 3-year warranty for this product.



Voltage range and voltage type



LED type



The structural design of this product ensures effective heat dissipation.




Beam angle




Lifespan

Parameter	Value
Luminous efficacy	90 lm/W
Power	12 W
Colour of the light	White
Energy efficiency class 2019/2015	F
Luminous flux	1160 lm
Correlated colour temperature	3000 K
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
Dimmable function	No
Survival factor	0.9
Lifetime L70B50	30 000
Supply voltage range and voltage type	220-240 AC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	white
The lumen maintenance factor	96
Lamp's diameter	19
Beam angle	270 °
Material (housing)	Ceramic
LED type	SMD2835
Lifespan	30000
Power Factor	0,5


Parameter	Value
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
For indoor use	Inside
Full box quantity	250 pc
Lamp's warm-up time to 60%	1
Height	75 mm
Product weight with packaging (g)	38 g
Master carton weight (kg)	9,5
EPREL ID	1 551 400
Energy class	A+
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	MLS
Connected light source (EPREL)	No
Colour-tunable light source (EPREL)	No
R9 colour rendering index value (EPREL)	5
Total luminous flux (EPREL)	1160
On-mode power Pon (EPREL)	12
Useful luminous flux Φuse (EPREL)	1160
Beam angle in degrees (EPREL)	270



Single packaging



Bulk packaging



Europallet

