

LED line PRIME

Code: 210202-CAW3HAT

EAN: 5905378220133

Waterproof fixture RANGER 10-40W CCT 6000lm 120cm PRIME



RANGER 10-40W CCT 6000lm 120cm IP66 PRIME is an ideal solution for demanding users, providing high light performance of 150 lm/W. It is characterized by a durable polycarbonate housing and IP66 protection, which guarantees resistance to water and dust.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	<div><ul style="list-style-type: none">10-40 W</div>
Voltage	<div><ul style="list-style-type: none">220-240 V AC</div>
Correlated colour temperature	<div><ul style="list-style-type: none">3000 K4000 K5000 K</div>
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP66
IK protection rating	10
IEC protection class	II
Luminous efficacy	150
Luminous flux	6000
The lumen maintenance factor	96
Lifetime L70B50	100 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Emergency module test	Autotest
Operating time in emergency mode	3 h
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2835
LED quantity	312
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-25÷45
Colour	Grey
Material (housing)	Polycarbonate
Material (cover)	Polycarbonate

LED line PRIME

Code: 210202-CAW3HAT

EAN: 5905378220133

**Waterproof fixture RANGER 10-40W CCT
6000lm 120cm PRIME**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 210202-CAW3HAT

EAN: 5905378220133

**Waterproof fixture RANGER 10-40W CCT
6000lm 120cm PRIME**

Example application