

LED line PRIME

Code: 202559

EAN: 5905378202559

LED line PRIME Floodlight 30W 4000K
4200lm T3



Technical data

Parameter	Value
Luminous efficacy	140 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	4200 lm
Colour consistency in McAdam ellipses	≤6
IP protection rating	IP66
Warranty (years)	5
Survival factor	0.9
Lifetime L70B50	50 000
Wire length	890 mm
Weight	1 g
Mounting type	surface
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	70
The lumen maintenance factor	96 %
Beam angle	105*155 °
Material (cover)	tempered glass

Parameter	Value
Material (housing)	aluminum
LED type	SMD2835
LED quantity	96
Power Factor	0,9
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-40÷45 °C
For indoor and outdoor use	YES
IEC protection class	I
Full box quantity	10 pc
Length	252 mm
Width	213 mm
Height	43,5 mm
Power	• 30 W
Voltage	• 100-227 V AC
Correlated colour temperature	• 4000 K

LED line PRIME

Code: 202559


EAN: 5905378202559

LED line PRIME Floodlight 30W 4000K
4200lm T3


Dimensions

Light distribution

Additional product photos




Logistics data




Single packaging

Width	252 mm
Height	43,5 mm mm
Length	213 mm mm
Weight	1 kg kg



Bulk packaging

Number of pieces/tape in meters pack zb	10 szt.
Width	480 mm mm
Height of collective packaging	285 mm
Length	320 mm mm
Weight	10,35 kg kg
Volume	0,043 m3 m3



Europallet

Number of pieces/tapes in meters euro pallet	200
Quantity collective euro pallet	240 szt.
Weight of a euro pallet	248,4 kg kg
Pallet height	1710 mm
Quantity in 1 layer	40 szt.
Number of layers	6

LED line PRIME

Code: 202559

EAN: 5905378202559

**LED line PRIME Floodlight 30W 4000K
4200lm T3**

Example application