

LED line PRIME

Code: 205819

EAN: 5905378205819

LED line PRIME Panel Backlit 34W
4000K 4760lm 60x60

New



Technical data

Parameter	Value
Luminous efficacy	140 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	C
Luminous flux	4760 lm
Colour consistency in McAdam ellipses	≤6
IP protection rating	IP20
Warranty (years)	5
Dimmable function	Triac
Survival factor	0.9
Lifetime L70B50	50 000
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White
The lumen maintenance factor	96 %
Beam angle	90 °
Material (cover)	polystyrene

Parameter	Value
Material (housing)	aluminum
LED type	SMD LED 2835
LED quantity	128
Power Factor	0,9
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
IEC protection class	II
IK protection rating	02
Lamp's warm-up time to 60%	1
Height	30 mm
Power	• 34 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K

LED line PRIME

Code: 205819

EAN: 5905378205819


LED line PRIME Panel Backlit 34W
4000K 4760lm 60x60

Dimensions

Light distribution


Additional product photos

Logistics data




Single packaging

Width	30
Height	640 mm
Length	600 mm
Weight	1,41 kg
	1



Bulk packaging

Number of pieces/tape in meters pack zb	5
Width	170 mm
Height of collective packaging	655
Length	615 mm
Weight	9,6 kg
Volume	0,075 m3 m3



Europallet

Quantity collective euro pallet	60 szt.
Weight of a euro pallet	115,2 kg kg
Pallet height	1340 mm
Quantity in 1 layer	30 szt.
Number of layers	2

LED line PRIME

Code: 205819

EAN: 5905378205819

**LED line PRIME Panel Backlit 34W
4000K 4760lm 60x60**

Example application