

LED line PRIME

Code: 203266-DALI

EAN: 5905378224117

**Linear luminaire FUSION 4000K 40W
5200lm 120° IP20 120cm white PRIME
PC Cover DALI**



FUSION fixture series is available in power ranges from 20 to 60W, with a color temperature of **4000K**. The efficiency of the fixtures is 130 lm/W.

DALI version.

Product made to order - delivery within 4 days.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5/7*
Power	• 40 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	I
Luminous efficacy	130
Luminous flux	5200
Lifetime L70B50	50 000 h

Parameter	Value
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h
Dimmable function	Dali
Sling length	200 cm
Frequency of the supply voltage	50/60Hz
Beam angle	120°
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20 ÷ 45
For indoor use	Inside
Height	52 mm
DALI	• YES

LED line PRIME


Code: 203266-DALI

EAN: 5905378224117

**Linear luminaire FUSION 4000K 40W
5200lm 120° IP20 120cm white PRIME
PC Cover DALI**



Technical drawing

Light distribution



Additional product photos

Logistics data



Single packaging

Width	1158 mm
Height	52 mm
Length	70 mm
Weight	1,82 kg

Bulk packaging

Quantity	12
Width	1260 mm
Height	260 mm
Length	260 mm
Weight	18,6 kg

Europallet

Quantity	144
Height	1,6 m
Bulk quantity	12
Weight	248 kg

LED line PRIME

Code: 203266-DALI

EAN: 5905378224117

**Linear luminaire FUSION 4000K 40W
5200lm 120° IP20 120cm white PRIME
PC Cover DALI**

Example application