


LED line® strip 150 SMD 12V red 2,4W

Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



Manufacturer issues a 5-year warranty for this product.



Beam angle



Voltage range and voltage type



Ambient temperature suitable for operation



LED type



Lifespan




LED quantity (1m)




Dimmable

| Parameter | Value |
|---------------------------------------|---------|
| Colour of the light | Red |
| IP protection rating | 20 |
| Warranty (years) | 5 |
| Dimmable function | PWM |
| Minimum purchase quantity | 5 |
| Lifetime L70B50 | 50 000 |
| Wattage (1m) | 2,4 W |
| Current (1m) | 0,2 |
| Supply voltage range and voltage type | 12 VDC |
| Metres per roll | 5 |
| The lumen maintenance factor | >0,7 % |
| Beam angle | 120 ° |
| LED type | SMD3528 |
| Not dimmable | TAK |
| Compatible dimmer type | PWM |
| Laminate (colour) | White |


| Parameter | Value |
|--|------------|
| Laminate (thickness) | 2 |
| LED quantity (1m) | 30 |
| Cutting section | 10 |
| Type of adhesive tape | 3M 300 LSE |
| Lifespan | 100000 |
| Number of on/off cycles | 50000 |
| Colour consistency in McAdam ellipses | ≤3 |
| Ambient temperature suitable for operation | -20÷45 °C |
| For indoor use | Inside |
| IEC protection class | III |
| Full box quantity | 75 pc |
| Lamp's warm-up time to 60% | 1 |
| Width | 8 mm |
| Height | 2,5 mm |
| Product weight with packaging | 103 g |
| Master carton weight (kg) | 7,73 |



Single packaging




Bulk packaging



100

Europallet



24
984
8
3