

LED line PRIME

Code: 200319

EAN: 5905378200319

LED line PRIME Floodlight 50W 4000K
7000lm 90°



product_card.label_technical_data

Parameter	Value	Parameter	Value
Luminous efficacy	140 lm/W	LED type	SMD2835
Colour of the light	White	LED quantity	96
Energy efficiency class 2019/2015	D	Power Factor	0,9
Luminous flux	7000 lm	Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6	Colour consistency in McAdam ellipses	≤6
IP protection rating	IP66	Ambient temperature suitable for operation	-40÷45 °C
Warranty (years)	5	For indoor and outdoor use	YES
Survival factor	0.9	IEC protection class	I
Lifetime L70B50	50 000	IK protection rating	08
Wire length	920 mm	Full box quantity	10 pc
Weight	1 g	Lamp's warm-up time to 60%	1
Mounting type	surface	Length	252 mm
Frequency of the supply voltage	50/60Hz	Width	213 mm
Colour rendering index Ra	70	Height	43,5 mm
The lumen maintenance factor	96 %	Power	• 50 W
Beam angle	90 °	Voltage	• 100-227 V AC
Material (cover)	tempered glass	Correlated colour temperature	• 4000 K
Material (housing)	aluminum		

LED line PRIME

Code: 200319


EAN: 5905378200319

LED line PRIME Floodlight 50W 4000K
7000lm 90°




product_card.label_dimensions

product_card.label_curve_light

product_card.label_product_gallery



product_card.label_logistic_data



Single packaging

Width	252 mm
Height	43,5 mm mm
Length	213 mm mm
Weight	1 kg kg

Bulk packaging

Number of pieces/tape in meters pack zb	10 szt.
Width	480 mm mm
Height of collective packaging	285 mm
Length	320 mm mm
Weight	10,35 kg kg
Volume	0,043 m3 m3

Europallet

Number of pieces/tapes in meters euro pallet	200
Quantity collective euro pallet	240 szt.
Weight of a euro pallet	248,4 kg kg
Pallet height	1710 mm
Quantity in 1 layer	40 szt.
Number of layers	6

LED line PRIME

Code: 200319

EAN: 5905378200319

LED line PRIME Floodlight 50W 4000K
7000lm 90°

Example application