

LED line PRIME LED Tube T8 22W 4000K 3300lm 220-240V 150cm



Manufacturer issues a 5-year warranty for this product.



Voltage range and voltage type



LED type



LED quantity



Beam angle



Lamp type




Lifespan

Parameter	Value
Luminous efficacy	150 lm/W
Power	22 W
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	3300 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	20
Warranty (years)	5
Survival factor	0.9
Minimum purchase quantity	25
Lifetime L70B50	25 000
Material	Glass
Supply voltage range and voltage type	220-240 VAC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80


Parameter	Value
The lumen maintenance factor	96 %
Lamp's type	T8
Beam angle	270 °
Material (cover)	glass
Material (housing)	Glass
LED type	SMD2835
LED quantity	120
Lifespan	25000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
For indoor use	Inside
Full box quantity	25 pc
Lamp's warm-up time to 60%	1
Length	1500 mm
Product weight with packaging	225 g
Master carton weight (kg)	6,3

Single packaging




Width	47 mm
Height	36 mm
Length	47 mm
Weight	0,24 kg
	1

Bulk packaging



Number of pieces/tape in meters pack zb	25 szt.
Width	1590 mm
Height of collective packaging	175 mm
Length	170 mm
Weight	8,4 kg
Volume	0,047 m ³

Europallet



Quantity collective euro pallet	600 szt.
Weight of a euro pallet	101 kg
Pallet height	1590 mm
Quantity in 1 layer	600 szt.
Number of layers	1