

LED line LITE

Code: 247910

EAN: 5901583247910

**LED bulb G9 4000K 8W 750lm 230V
270° Ceramic LITE**



LED line bulb LITE G9 8W 4000K 750lm is a modern light source that stands out for high energy efficiency of 94 lm/W. With a light stream of 750 lumens and a lighting angle of 270°, it ensures a uniform distribution of light in the room. Made of durable ceramics, it has a lifespan of up to 30,000 hours and resistance to mechanical damage.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 8 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
Luminous efficacy	94
Luminous flux	750 lm
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	270 °
LED type	SMD2835
Power Factor	0,5
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	70 mm
Colour	white
Material (housing)	Ceramics

LED line LITE

Code: 247910


EAN: 5901583247910

**LED bulb G9 4000K 8W 750lm 230V
270° Ceramic LITE**

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	50 mm
Height	50 mm
Length	60 mm
Weight	0,027 kg

Bulk packaging

Quantity	500
Width	610 mm
Height	235 mm
Length	160 mm
Volume	0,022 m3
Weight	14,12 kg
Comments	

Europallet

Quantity	40000
Height	1,6 m
Quantity in layer	3000
Number of layers	13
Bulk quantity	80
Weight	1150 kg

LED line LITE

Code: 247910

EAN: 5901583247910

**LED bulb G9 4000K 8W 750lm 230V
270° Ceramic LITE**

Example application