

LED line PRIME Code: 470720 EAN: 5907777470720

LED line PRIME SMD 5W 2700K 400lm 220-260V 50mm DIM



LED line bulb PRIME SMD 5W 2700K is a unique light source with a stream of 400 lumens and a warm colour of 2700 K. Made of ceramics and glass, it provides high quality and aesthetic design. With a PF power factor of 0.5 and a light output of 80 lm/W, it offers an energy-efficient solution.











Technical data

Parameter	Value
Energy efficiency class 2019/2015	G
Energy class	A+
Warranty	3
Power	• 5W
Voltage	• 220-260 V AC
Correlated colour temperature	• 2700 K
Colour of the light	White
Colour rendering index Ra	80
IEC protection class	II
Luminous efficacy	80
Luminous flux	400
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	Triac
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Fixture's diameter	50 mm
Beam angle	110
LED type	SMD2835
Compatible dimmer type	TRIAC
Power Factor	0,5
Number of on/off cycles	50000
Ambient temperature suitable for operation	-5÷40
For indoor use	Inside
Colour	White
Material (housing)	Ceramics
Material (cover)	glass



LED line PRIME Code: 470720 EAN: 5907777470720


LED line PRIME SMD 5W 2700K 400lm 220-260V 50mm DIM

Technical drawing




Light distribution

Luminous [cd/klm]





Additional product photos






Logistics data







Single packaging

Bulk packaging

Europallet

MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME Code: 470720 EAN: 5907777470720

LED line PRIME SMD 5W 2700K 400lm 220-260V 50mm DIM

Example application