

LED line PRIME

Code: 477149

EAN: 5907777477149

LED line strip 600 SMD 12V 4000K 9,6W



3-step
MacAdam

* IES
↓

5-year
warranty

product_card.label_technical_data

Parameter	Value
Luminous efficacy	100 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	F
Colour consistency in McAdam ellipses	≤3
IP protection rating	IP20
Warranty (years)	5
Dimmable function	PWM
Survival factor	0.9
Minimum purchase quantity	5
Lifetime L70B50	30 000
Wire length	5 000 mm
Wattage (lm)	9,6 W
Luminous flux (lm)	960
Current (lm)	0,8
Colour rendering index Ra	80
Metres per roll	5
The lumen maintenance factor	96 %
Beam angle	120 °

Parameter	Value
LED type	SMD 2835
LED quantity	600
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (lm)	120
Cutting section	2,5
Type of adhesive tape	3M 300 LSE
Colour consistency in McAdam ellipses	≤3
Ambient temperature suitable for operation	-25÷45 °C
For indoor use	Inside
IEC protection class	III
Length	5000 mm
Width	8 mm
Height	2,5 mm
Power	9.6
Voltage	12 V DC
Correlated colour temperature	4000 K

LED line PRIME


Code: 477149

EAN: 5907777477149



LED line strip 600 SMD 12V 4000K 9,6W

product_card.label_dimensions


product_card.label_curve_light



product_card.label_product_gallery




product_card.label_logistic_data




Single packaging

Width	153 mm
Height	15 mm
Length	153 mm
Weight	0,13 kg



Bulk packaging

Number of pieces/tape in meters pack zb	40 szt.
Width	360 mm
Height of collective packaging	180 mm
Length	320 mm
Weight	5,1 kg
Volume	0,020 m3



Europallet

Number of pieces/tapes in meters euro pallet	12000 m
Quantity collective euro pallet	2400 szt.
Weight of a euro pallet	300 kg
Pallet height	1800 mm
Quantity in 1 layer	240 szt.
Number of layers	10

LED line PRIME

Code: 477149

EAN: 5907777477149

LED line strip 600 SMD 12V 4000K 9,6W

Example application