

LED line PRIME

Code: 202696

EAN: 5905378202696

LED line PRIME Floodlight 400W 4000K 56000lm T3



The PRIME Floodlight 400W LED line reflector is a versatile lighting setting offering an impressive light stream of 56,000 lumens. Thanks to the colour of the light 4000 K and the colour reproduction coefficient Ra at level 70, it provides natural color rendering. Energy efficiency class D and power factor PF 0.9 confirm the efficiency of the device.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 400 W
Voltage	• 100-227 V AC
Correlated colour temperature	• 4000K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	08
IEC protection class	I
Luminous efficacy	140
Luminous flux	56000

Parameter	Value
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2835
LED quantity	720
Number of on/off cycles	50000
Ambient temperature suitable for operation	-40÷45
Material (housing)	Aluminium
Material (cover)	tempered glass

LED line PRIME

Code: 202696


EAN: 5905378202696

**LED line PRIME Floodlight 400W 4000K
56000lm T3**

Technical drawing




Light distribution




Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 202696

EAN: 5905378202696

**LED line PRIME Floodlight 400W 4000K
56000lm T3**

Example application