

LED line PRIME LED bulb E27 7W 4000K 1470lm 220-240V FILAMENT A60 GLOBE



High user-safety guaranteed.



Manufacturer issues a 5-year warranty for this product.



Voltage range and voltage type



Lamp type



Lifespan



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Beam angle



Ambient temperature suitable for operation



LED type




LED quantity

Parameter	Value
Luminous efficacy	210 lm/W
Power	7 W
Colour of the light	White
Energy efficiency class 2019/2015	A
Luminous flux	1470 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	20
Warranty (years)	5
Dimmable function	PWM
Survival factor	0.9
Lifetime L70B50	40 000
Weight	35 g
Material	Glass
Supply voltage range and voltage type	220-240 VAC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80


Parameter	Value
The lumen maintenance factor	96 %
Lamp's type	A60
Lamp's diameter	60
Beam angle	360 °
Material (cover)	glass
LED type	Filament
LED quantity	6
Lifespan	40000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
Full box quantity	50 pc
Lamp's warm-up time to 60%	1
Height	108 mm
Product weight with packaging	50 g
Master carton weight (kg)	3,5

Single packaging




Width 50 mm
 Height 63 mm
 Length 50 mm
 Weight 0,03 kg
 1

Bulk packaging



Number of pieces/tape in meters pack 50 szt.
 Width 325 mm
 Height of collective packaging 240 mm
 Length 325 mm
 Weight 3,01 kg
 Volume 0,025 m³

Europallet



Quantity collective euro pallet 2400 szt.
 Weight of a euro pallet 144,48 kg
 Pallet height 1920 mm
 Quantity in 1 layer 300 szt.
 Number of layers 8