




1

Code: 243424 EAN: 5901583243424

LED line® module OPTO 3x SMD2835 12V 6500K 2,5W

Applications:

- 3D lightboxes
- Backlighting of advertisements and inscriptions
- Aquarium backlighting
- LED signs, lumions
- Outdoor lighting







Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



High luminous efficacy ensured by high quality OSRAM branded LEDs. $\,$



Beam angle



Ambient temperature suitable for operation



Lifespan



This product is featured by a high degree of IP protection, which makes it suitable for a broader range of lighting applications and offers high safety of use.



Manufacturer issues a 7-year warranty for this product.



Voltage range and voltage type



LED type




LED quantity

| Parameter | Value |
|---------------------------------------|---------|
| Luminous efficacy | 95 lm/W |
| Power | 2,5 W |
| Colour of the light | White |
| Energy efficiency class 2019/2015 | F |
| Luminous flux | 237 lm |
| Correlated colour temperature | 6500 K |
| Colour consistency in McAdam ellipses | ≤6 |
| IP protection rating | 65 |
| Warranty (years) | 7 |
| Dimmable function | PWM |
| Survival factor | 0.9 |
| Lifetime L70B50 | 70 000 |
| Supply voltage range and voltage type | 12 VDC |
| Colour rendering index Ra | 80 |
| The lumen maintenance factor | 96 % |
| Beam angle | 170 ° |


| Parameter | Value |
|--|-----------|
| Material (housing) | PVC |
| LED type | SMD2835 |
| LED quantity | 3 |
| Compatible dimmer type | PWM |
| Lifespan | 70000 |
| Number of on/off cycles | 50000 |
| Colour consistency in McAdam ellipses | ≤6 |
| Ambient temperature suitable for operation | -40÷55 °C |
| For indoor and outdoor use | YES |
| Lamp's warm-up time to 60% | 1 |
| Length | 85 mm |
| Width | 20 mm |
| Height | 5 mm |
| Product weight with packaging | 21 g |
| Master carton weight (kg) | 2,1 |
| Energy class | A++ |



Luminous [cd/klm]



Single packaging



 Width
 85 mm


 Height
 5 mm

 Length
 20 mm

 Weight
 0,02 kg

 120

Bulk packaging




Number of pieces/tape in meters pack zb

Width 520 mm
Height of collective packaging 260 mm
Length 400
mm

Weight 19,55 kg
Volume 1,297 m3

Europallet



| Number of pieces/tapes in meters euro pallet | 240 |
|--|-----------|
| Quantity collective euro pallet | 20160 |
| Weight of a euro pallet | 435,6 |
| Pallet height | 182 cm |
| Quantity in 1 layer | 2880 |
| Number of lavers | 7 |