

LED line LITE LED bulb E14 5W 4000K 600lm 220-240V FILAMENT C35 CANDLE DIMMABLE



Manufacturer issues a 3-year warranty for this product.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Voltage range and voltage type



Lamp type



Lifespan



High user-safety guaranteed.



Beam angle



Ambient temperature suitable for operation



LED type




LED quantity

Parameter	Value
Luminous efficacy	120 lm/W
Power	5 W
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	600 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	20
Warranty (years)	3
Dimmable function	Triac
Survival factor	0.9
Lifetime L70B50	25 000
Weight	12 g
Material	Glass
Supply voltage range and voltage type	220-240 VAC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80

Parameter	Value
The lumen maintenance factor	96 %
Lamp's type	C35
Lamp's diameter	35
Beam angle	360 °
Material (cover)	glass
LED type	Filament
LED quantity	4
Lifespan	25000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
Full box quantity	100 pc
Lamp's warm-up time to 60%	1
Height	98 mm
Product weight with packaging	22 g
Master carton weight (kg)	3

Single packaging



Width	60 mm
Height	125 mm
Length	60 mm
Weight	0,02 kg
	1

Bulk packaging



Number of pieces/tape in meters pack zb	100 szt.
Width	380 mm
Height of collective packaging	225 mm
Length	200 mm
Weight	2,54 kg
Volume	0,017 m ³

Europallet



Quantity collective euro pallet	9600 szt.
Weight of a euro pallet	243,84 kg
Pallet height	1800 mm
Quantity in 1 layer	1200 szt.
Number of layers	8