

LED line PRIME

Code: 203051

EAN: 5905378203051

LED line PRIME Floodlight 150W CCT 21000lm T3



The PRIME Floodlight 150W LED line light combines high performance with modern lighting technology. It emits an impressive 21000 lm light stream, which translates into efficiency as much as 140 lm/W. Its IP66 seal class provides resistance to difficult weather conditions. Thanks to materials such as aluminum and tempered glass, the device guarantees long-term operation and safety.



Technical data

| Parameter | Value |
|-----------------------------------|---|
| Energy efficiency class 2019/2015 | D |
| Warranty | 5 |
| Power | <ul style="list-style-type: none">150 W |
| Voltage | <ul style="list-style-type: none">100-227 V AC |
| Correlated colour temperature | <ul style="list-style-type: none">3000 K4000K5000 K |
| Colour of the light | White |
| Colour rendering index Ra | 70 |
| IP protection rating | IP66 |
| IK protection rating | 08 |
| IEC protection class | I |
| Luminous efficacy | 140 |
| Luminous flux | 21000 |
| The lumen maintenance factor | 96 |
| Lifetime L70B50 | 50 000 h |

| Parameter | Value |
|--|----------------|
| Survival factor | 0.9 |
| Colour consistency in McAdam ellipses | ≤6 |
| Mounting type | surface |
| Frequency of the supply voltage | 50/60Hz |
| Beam angle | 70°155 |
| LED type | SMD2835 |
| LED quantity | 360 |
| Power Factor | 0,9 |
| Number of on/off cycles | 50000 |
| Lamp's warm-up time to 60% | 1 s |
| Ambient temperature suitable for operation | -40÷45 |
| Material (housing) | Aluminium |
| Material (cover) | tempered glass |

LED line PRIME

Code: 203051

EAN: 5905378203051

**LED line PRIME Floodlight 150W CCT
21000lm T3**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 203051

EAN: 5905378203051

**LED line PRIME Floodlight 150W CCT
21000lm T3**

Example application