



LED line® strip 300 SMD 12V RGB 14,4W DIGITAL P943



LED Strip line is a modern and versatile linear **light source**, used for interior lighting, furniture, lightboxes, illuminated signs, and public spaces.



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



LED line® DIGITAL strip is based on SPI protocol and WS2811 component, which enables independent control of each 3-diode section of the strip. DIGITAL strip allows to produce advanced dynamic and "floating" unique lighting effects.



This LED strip produces light from RGB colour palette.

Manufacturer issues a 5-year warranty for this product.



Voltage range and voltage type



Beam angle



Ambient temperature suitable for operation



LED type



Lifespan



LED quantity (1m)




Dimmable

Parameter	Value
Colour of the light	RGB
IP protection rating	20
Warranty (years)	5
Minimum purchase quantity	5
Lifetime L70B50	50 000
Wattage (1m)	14,4 W
Current (1m)	1,2
Supply voltage range and voltage type	12 DC
Metres per roll	5
Beam angle	120 °
LED type	SMD5050
Not dimmable	TAK
Compatible dimmer type	P943 IC
Laminate (colour)	White
Laminate (thickness)	2


Parameter	Value
LED quantity (1m)	60
Cutting section	5
Type of adhesive tape	3M 300 LSE
Lifespan	100000
Number of on/off cycles	50000
Ambient temperature suitable for operation	-20 ÷ 45 °C
For indoor use	Inside
IEC protection class	III
Full box quantity	75 pc
Lamp's warm-up time to 60%	1
Width	10 mm
Height	2,5 mm
Product weight with packaging (g)	146 g
Master carton weight (kg)	10,95

Luminous [cd/klm]




C0 - C180 C90 - C270

Single packaging




1

Bulk packaging



100

Europallet



6