

LED line PRIME

Code: 202443

EAN: 5905378202443

**FLOODLIGHT 4000K 50W 7000lm T2
IP66 PRIME**



The PRIME Floodlight 50W LED line provides an impressive light stream of 7000 lm, which translates into high energy efficiency of 140 lm/W. Thanks to IP66 leak class, it is resistant to adverse weather conditions, which ensures its reliability in both internal and external applications. Equipped with durable SMD2835 diodes and aluminum casing, it has a long life of up to 50,000 hours.



Technical data

| Parameter | Value |
|--|----------------|
| Energy efficiency class 2019/2015 | D |
| Warranty | 5/7* |
| Power | • 50 W |
| Voltage | • 100-277 V AC |
| Correlated colour temperature | • 4000 K |
| Colour of the light | White |
| Colour rendering index Ra | 70 |
| IP protection rating | IP66 |
| IEC protection class | I |
| Luminous efficacy | 140 |
| Luminous flux | 7000 |
| The lumen maintenance factor | 96 |
| Lifetime L70B50 | 50 000 h |
| L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible | 35000 h |

| Parameter | Value |
|--|----------------|
| Survival factor | 0.9 |
| Colour consistency in McAdam ellipses | ≤6 |
| Wire length | 920 mm |
| Mounting type | surface |
| Frequency of the supply voltage | 50/60Hz |
| Beam angle | 70°/155 |
| LED type | SMD2835 |
| LED quantity | 96 |
| Power Factor | 0.9 |
| Number of on/off cycles | 50000 |
| Ambient temperature suitable for operation | -40÷45 |
| Height | 42 mm |
| Material (housing) | Aluminium |
| Material (cover) | Tempered glass |


LED line PRIME

Code: 202443


EAN: 5905378202443

**FLOODLIGHT 4000K 50W 7000lm T2
IP66 PRIME**

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

| | |
|--------|---------|
| Width | 252 mm |
| Height | 43,5 mm |
| Length | 213 mm |
| Weight | 1 kg |

Bulk packaging

| | |
|----------|----------|
| Quantity | 10 |
| Width | 480 mm |
| Height | 285 mm |
| Length | 320 mm |
| Volume | 0,043 m3 |
| Weight | 10,35 kg |
| Comments | |

Europallet

| | |
|-------------------|----------|
| Quantity | 200 |
| Height | 1710 mm |
| Quantity in layer | 40 |
| Number of layers | 6 |
| Bulk quantity | 240 |
| Weight | 248,4 kg |

LED line PRIME

Code: 202443

EAN: 5905378202443

**FLOODLIGHT 4000K 50W 7000lm T2
IP66 PRIME**

Example application