

LED line PRIME LED bulb E14 5W 2700K 700lm 170-250V C37 Candle



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Manufacturer issues a 5-year warranty for this product.



Voltage range and voltage type



Lamp type



Lifespan



The structural design of this product ensures effective heat dissipation.



Beam angle



Ambient temperature suitable for operation



LED type

Parameter	Value
Luminous efficacy	140 lm/W
Power	5 W
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	700 lm
Correlated colour temperature	3000 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	20
Warranty (years)	5
Survival factor	0.9
Lifetime L70B50	30 000
Material	Ceramic
Supply voltage range and voltage type	170-250 VAC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White
The lumen maintenance factor	96 %

Parameter	Value
Lamp's type	C37
Lamp's diameter	37
Beam angle	220 °
Material (cover)	glass
Material (housing)	Ceramic
LED type	SMD2835
Lifespan	30000
Power Factor	0,5
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
Full box quantity	100 pc
Lamp's warm-up time to 60%	1
Height	111 mm
Master carton weight (kg)	7

Single packaging



Bulk packaging



Outer box quantity

100 pcs.

Europallet

