

LED line PRIME

Code: 201057-CAW3HAT

EAN: 5905378216136

**LINKER TRI-PROOF 80W 4000K
12000lm 150lm/W 220-240V IP65 150cm
Emergency module 3H AT PRIME**



LINKER 80W is a modern LED lighting with a colour temperature of 4000 K, emitting an impressive light stream of 12000 lm. With high energy efficiency of 150 lm/W and D efficiency class, it saves energy while maintaining intensive lighting. The product has a high degree of protection IP65, making it resistant to water and dust.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 80 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IEC protection class	II
Luminous efficacy	150
Luminous flux	12000
The lumen maintenance factor	96
Lifetime L70B50	100 000 h
Survival factor	0.9
Dimmable function	PWM

Parameter	Value
Colour consistency in McAdam ellipses	≤6
ULOR	3 %
Emergency module test	Autotest
Operating time in emergency mode	3 h
Frequency of the supply voltage	50/60Hz
Beam angle	120
Lifespan	100 000 h
Power Factor	0,95
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-25 ÷ 45
Colour	Grey
Material (housing)	Polycarbonate
Material (cover)	Polycarbonate

LED line PRIME

Code: 201057-CAW3HAT

EAN: 5905378216136


**LINKER TRI-PROOF 80W 4000K
12000lm 150lm/W 220-240V IP65 150cm
Emergency module 3H AT PRIME**

Technical drawing


Light distribution

Additional product photos


Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 201057-CAW3HAT

EAN: 5905378216136

**LINKER TRI-PROOF 80W 4000K
12000lm 150lm/W 220-240V IP65 150cm
Emergency module 3H AT PRIME**

Example application