


**LED line® E14 5W 425lm 4000K 220-240V R39**

The structural design of this product ensures effective heat dissipation.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Voltage range and voltage type



Lamp type



Lifespan



Manufacturer issues a 3-year warranty for this product.



Beam angle



Ambient temperature suitable for operation



LED type


Parameter	Value
Luminous efficacy	85 lm/W
Power	5 W
Colour of the light	White
Energy efficiency class 2019/2015	F
Luminous flux	425 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
Survival factor	0.9
Lifetime L70B50	30 000
Supply voltage range and voltage type	170-250 VAC

Parameter	Value
Beam angle	220 °
Material (cover)	glass
Material (housing)	Ceramic
LED type	SMD2835
Lifespan	30000
Power Factor	0,5
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
Full box quantity	100 pc

Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	white
The lumen maintenance factor	96 %
Lamp's type	R39
Lamp's diameter	39


Lamp's warm-up time to 60%	1
Height	68 mm
Product weight with packaging	50 g
Master carton weight (kg)	5
Energy class	A+

Luminous [cd/klm]




C0 - C180 C90 - C270

Single packaging




Width	39 mm
Height	148 mm
Length	195 mm
Weight	0,55 kg
	10

Bulk packaging



Width	100
	215 mm
Length	170
	415 mm
Weight	6,5 kg
Volume	0,01516825 m3

Europallet



Weight of a euro pallet	63
	409,5 kg
	1674
	7
	9