

LED line PRIME

Code: 203457-DALI

EAN: 5905378220027

**Panel Backlit 42W 4000K 6300lm
UGR<19 60x60 DALI PRIME**



The PRIME Backlit LED line panel with 42W power and 6300 lm light stream is a modern lighting solution that is characterized by the colour of light 4000K. Low glare rate UGR<19 provides comfort of use in intensely exploited spaces. In standard dimensions 595x595 mm, made of high quality materials, guarantees long-term use and energy efficiency at Class B level.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	B
Warranty	5
Power	• 42 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	150
Luminous flux	6300
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	90
LED type	SMD LED 2835
LED quantity	108
Power Factor	0.9
Number of on/off cycles	25000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-25÷45
For indoor use	Inside
Colour	White
Material (housing)	Aluminium
Material (cover)	Polystyrene

LED line PRIME

Code: 203457-DALI

EAN: 5905378220027

**Panel Backlit 42W 4000K 6300lm
UGR<19 60x60 DALI PRIME**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 203457-DALI

EAN: 5905378220027

**Panel Backlit 42W 4000K 6300lm
UGR<19 60x60 DALI PRIME**

Example application