

LED line LITE


Code: 210127

EAN: 5905378210127

LED line LITE Downlight EASY FLEX 18-21-24W CCT 2110lm round white



Downlight EASY FLEX 18-21-24W CCT is a modern LED line LITE lighting luminaire, characterized by a luminous flux performance of 2110 lumens. It allows to choose colour temperature in the range 3000 K, 4000 K and 5000 K, which provides flexibility in space arrangement. IP20 seal class guarantees protection against solid bodies larger than 12 mm and the IK05 protection level provides impact resistance.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	18 W 21 W 24 W
Voltage	220-240 V AC
Correlated colour temperature	3000 K 4000 K 5000 K
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	05
IEC protection class	II
Luminous efficacy	90
Luminous flux	2110
The lumen maintenance factor	96

Parameter	Value
Lifetime L70B50	30 000 h
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2835
LED quantity	168
Number of on/off cycles	15000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
Installation method	3in1 surface mounted, flush mounted, suspended
Mounting hole diameter	65-240
Colour	White


LED line LITE

Code: 210127


EAN: 5905378210127

LED line LITE Downlight EASY FLEX 18-21-24W CCT 2110lm round white

Technical drawing




Light distribution




Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line LITE

Code: 210127

EAN: 5905378210127

**LED line LITE Downlight EASY FLEX 18-
21-24W CCT 2110lm round white**

Example application