

LED line PRIME


Code: 203112-II

EAN: 5905378220089

**Road luminaire CAMINO 3CCT(3/4/5.7K)
100W 14000lm IP66 grey PRIME**



CAMINO CCT are fixtures designed for harsh weather conditions, **available in three power variants: 50W, 100W, 150W**. Equipped with carefully selected and quality-tested components, they ensure **reliability of operation** and a long lifespan of the fixtures



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5/7*
Power	• 100 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 3000 K • 4000 K • 5700 K
Colour of the light	CCT
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	08
IEC protection class	I
Luminous efficacy	140
Luminous flux	14000lm : 4000K - 13000lm: 3000K , 5700K

Parameter	Value
Lifetime L70B50	100 000 h
Frequency of the supply voltage	50/60Hz
Beam angle	150 x 110
LED type	LUMILEDS 2835
LED quantity	144
Power Factor	0,95
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-25÷45
For indoor use	Outside
Height	90 mm
Material (housing)	Aluminium
Material (cover)	Tempered glass


LED line PRIME

Code: 203112-II


EAN: 5905378220089

**Road luminaire CAMINO 3CCT(3/4/5.7K)
100W 14000lm IP66 grey PRIME**

Technical drawing



Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	256 mm
Height	116 mm
Length	611 mm
Weight	3,85 kg

Bulk packaging

Quantity	1
Weight	3,85 kg

Europallet

Quantity	48
Height	1900 mm
Bulk quantity	48
Weight	210 kg

LED line PRIME

Code: 203112-II

EAN: 5905378220089

**Road luminaire CAMINO 3CCT(3/4/5.7K)
100W 14000lm IP66 grey PRIME**

Example application