

LED line® G9 6W 3000K 550lm 220-240V

Manufacturer issues a 3-year warranty for this product.



Voltage range and voltage type



LED type



The structural design of this product ensures effective heat dissipation.




Beam angle



Lifespan

Parameter	Value
Luminous efficacy	92 lm/W
Power	6 W
Colour of the light	White
Energy efficiency class 2019/2015	F
Luminous flux	550 lm
Correlated colour temperature	3000 K
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
Dimmable function	No
Survival factor	0.9
Lifetime L70B50	30 000
Supply voltage range and voltage type	220-240 AC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	white
The lumen maintenance factor	96
Lamp's diameter	16
Beam angle	270 °
Material (housing)	Ceramic
LED type	SMD2835
Lifespan	30000
Power Factor	0,5
Number of on/off cycles	50000


Parameter	Value
Colour consistency in McAdam ellipses	≤6
For indoor use	Inside
Full box quantity	500 pc
Lamp's warm-up time to 60%	1
Height	66 mm
Product weight with packaging (g)	19 g
Master carton weight (kg)	9,5
EPREL ID	632 082
Date of first placement on the market	01.03.2021
Energy class	A+
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	MLS
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
R9 colour rendering index value (EPREL)	1
Total luminous flux (EPREL)	550
On-mode power Pon (EPREL)	6
Useful luminous flux Φuse (EPREL)	550
Beam angle in degrees (EPREL)	270



Single packaging



Bulk packaging



Europallet

