

LED line PRIME

Code: 206519-LAW3HAT

EAN: 5905378218413

Panel Backlit 34W 4000K 4760lm
UGR<19 120x30 Emergency module
PRIME LAW3HAT



The 34W and 4760 lm backlit LED panel is an effective lighting solution, providing a pleasant light with a colour temperature of 4000 K. The high light performance of 140 lm/W and the low glare rate of UGR<19 make it ideal for working spaces. Aluminium housing and polystyrene lid guarantee durability and modern aesthetics.



Technical data

Parameter	Value	Parameter	Value
Operating time in emergency mode	3 h	The lumen maintenance factor	96
Emergency module test	Auto Test	Beam angle	90
Voltage	• 200-240 V AC	Material (cover)	polystyrene
Luminous efficacy	140	Material (housing)	Aluminium
Colour of the light	White	LED type	SMD LED 2835
Energy efficiency class 2019/2015	D	LED quantity	72
Luminous flux	4760	Power Factor	0,9
Colour consistency in McAdam ellipses	≤6	Number of on/off cycles	50000
Warranty (years)	5	Colour consistency in McAdam ellipses	≤6
IP protection rating	IP20	Ambient temperature suitable for operation	-20÷40
Dimmable function	PWM	For indoor use	Inside
Survival factor	0.9	IEC protection class	II
Lifetime L70B50	50 000 h	IK protection rating	02
Frequency of the supply voltage	50/60Hz	Lamp's warm-up time to 60%	1 s
Colour rendering index Ra	80	Correlated colour temperature	• 4000 K
Colour	white	Power	• 34 W

LED line PRIME

Code: 206519-LAW3HAT

EAN: 5905378218413

**Panel Backlit 34W 4000K 4760lm
UGR<19 120x30 Emergency module
PRIME LAW3HAT**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 206519-LAW3HAT

EAN: 5905378218413

**Panel Backlit 34W 4000K 4760lm
UGR<19 120x30 Emergency module
PRIME LAW3HAT**

Example application