


LED line LITE Floodlight LUMINO 30W 4000K 3000lm with motion sensor



Thanks to the built-in PIR motion sensor, the light automatically turns on only when it detects motion, contributing to further energy savings. This feature not only provides convenience by eliminating the need to manually turn the light on and off, but also enhances safety by automatically illuminating dark corners indoors and outdoors.

IP44-level protection guarantees reliability and versatility in a variety of weather conditions, from -20°C to +40°C. This makes the lighting effective and durable, regardless of the weather and without worrying about its performance and safety.

It is also worth noting that LUMINO floodlights come with a 3-year warranty, which further confirms their reliability and high quality. With these products, it becomes possible to enjoy effective, energy-efficient and safe lighting for many years.



Beam angle



Ambient temperature suitable for operation



Lifespan



Voltage range and voltage type



LED type



LED quantity

Parameter	Value
Luminous efficacy	100 lm/W
Power	30 W
Colour of the light	White
Energy efficiency class 2019/2015	F
Luminous flux	3000 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	44
Warranty (years)	3
Survival factor	0.9
Lifetime L70B50	25 000
Weight	380 g
Supply voltage range and voltage type	220-240 VAC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	70
The lumen maintenance factor	96 %

Parameter	Value
Beam angle	110 °
Sensor type	PIR
Material (cover)	tempered glass
Material (housing)	DIE-CAST alu
LED type	SMD LED
LED quantity	28
Power Factor	0,9
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
IEC protection class	I
IK protection rating	05
Lamp's warm-up time to 60%	1
Length	164 mm
Width	167 mm
Height	79 mm

Single packaging



Width 169 mm
Height 172 mm
Length 63 mm
Weight 0,38 kg
1

Bulk packaging



Outer box quantity 20 pcs.
20
Width 360 mm
340
Length 370 mm
Weight 8,36 kg
Volume 0,45288 m³

Europallet

