

LED line

Code: 477163

EAN: 5907777477163

LED line strip 600 SMD 24V 2700K 9,6W

ATG F



Technical data

Parameter	Value	Parameter	Value
Luminous efficacy	100 lm/W	LED quantity	600
Colour of the light	White	Compatible dimmer type	PWM
Energy efficiency class 2019/2015	F	Laminate (colour)	White
Colour consistency in MacAdam ellipses	≤3	Laminate (thickness)	2
IP protection rating	IP20	LED quantity (lm)	120
Warranty (years)	5	Cutting section	5
Dimmable function	PWM	Type of adhesive tape	3M 300 LSE
Survival factor	0.9	Colour consistency in MacAdam ellipses	≤3
Minimum purchase quantity	5	Ambient temperature suitable for operation	-25÷45 °C
Lifetime L70B50	30 000	For indoor use	Inside
Wire length	200 mm	IEC protection class	III
Wattage (lm)	9,2 W	Length	5000 mm
Luminous flux (lm)	960	Width	8 mm
Current (lm)	0,4	Height	2,5 mm
Colour rendering index Ra	80	Energy class	F
Metres per roll	5	Power	• 9,6
The lumen maintenance factor	96 %	Voltage	• 24 V DC
Beam angle	120 °	Correlated colour temperature	• 2700 K
LED type	SMD 2835		

LED line


Code: 477163

EAN: 5907777477163


LED line strip 600 SMD 24V 2700K 9,6W

Dimensions


Light distribution



Additional product photos




Logistics data




Single packaging

5



Bulk packaging

Number of pieces/tape in meters pack zb	100
---	-----



Europallet

Number of pieces/tapes in meters euro pallet	2400
Quantity collective euro pallet	60
Weight of a euro pallet	300 kg
Pallet height	1800
Quantity in 1 layer	6
Number of layers	10

LED line

Code: 477163

EAN: 5907777477163

LED line strip 600 SMD 24V 2700K 9,6W

Example application