

LED line LITE


Code: 201088

EAN: 5905378201088

**Road luminaire STREETLITE 4000K
150W 15000lm IP65 grey LITE**



STREETLITE LED line LITE 150W is an advanced lighting solution that is distinguished by a high-quality aluminium housing for excellent heat removal. It is characterized by a high luminous efficiency of 100 lm/W and a total luminous flux of 15000 lm. Thanks to the IP65 protection degree, it is resistant to dust and moisture, and the IK08 resistance class protects against mechanical damage.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 150 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	08
IEC protection class	I
Luminous efficacy	100
Luminous flux	15000
The lumen maintenance factor	96
Lifetime L70B50	36 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
ULOR	0 %
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
CRI colour rendering index	80
Beam angle	130 x 75
LED type	SMD LED 2835
LED quantity	162
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-40÷50
Height	98
Colour	Grey
Material (housing)	Aluminium
Material (cover)	Polycarbonate


LED line LITE

Code: 201088


EAN: 5905378201088

**Road luminaire STREETLITE 4000K
150W 15000lm IP65 grey LITE**

Technical drawing




Light distribution



Additional product photos



Logistics data



Single packaging

Width	240 mm
Height	103 mm
Length	635 mm
Weight	1,73 kg

Bulk packaging

Quantity	3
Width	329 mm
Height	255 mm
Length	645 mm
Volume	0,054 m3
Weight	6,7 kg

Europallet

Quantity	63
Height	1,8 m
Quantity in layer	12
Number of layers	5
Bulk quantity	63
Weight	159 kg

LED line LITE

Code: 201088

EAN: 5905378201088

**Road luminaire STREETLITE 4000K
150W 15000lm IP65 grey LITE**

Example application

