

LED line PRIME

Code: LL-20-24

EAN: 5907777479198

LED power supply LED line PRIME LL-20-24 IP67 24V



product_card.label_technical_data

Parameter	Value	Parameter	Value
Output current range	0 ÷ 1A	Insulation strength	3kVAC
Warranty (years)	5	EMC standards	EN55015
Input voltage frequency range	47 ÷ 63Hz	Mounting type	surface
Rated current	1A	Inrush current (typ.)	15A / 230VAC
Safety standards	IP67	Ambient temperature suitable for operation	-30÷70 °C
Efficiency	0,84	IEC protection class	II
Voltage tolerance	-/+5.0%	Power	• 20 W
Ambient humidity	20 ÷ 90%	Voltage	• 90-264 V AC

LED line PRIME

Code: LL-20-24

EAN: 5907777479198

LED power supply LED line PRIME LL-20-24 IP67 24V


product_card.label_dimensions

product_card.label_curve_light

product_card.label_product_gallery




product_card.label_logistic_data




Single packaging

Width	45
Height	30 mm
Length	165 mm
Weight	0,21 kg
	1



Bulk packaging

Number of pieces/tape in meters pack zb	100
Width	290 mm
Height of collective packaging	230
Length	345 mm
Weight	22,5 kg



Europallet

Number of pieces/tapes in meters euro pallet	3200
Quantity collective euro pallet	32
Weight of a euro pallet	730 kg
Pallet height	1020

LED line PRIME

Code: LL-20-24

EAN: 5907777479198

LED power supply LED line PRIME LL-20-24 IP67 24V

Example application