


LED line LITE LED Bulb GU10 5W 6500K 450lm 220-240V



Beam angle



Ambient temperature suitable for operation



Voltage range and voltage type



Lifespan

Parameter	Value
Luminous efficacy	90 lm/W
Power	5 W
Colour of the light	White
Energy efficiency class 2019/2015	F
Luminous flux	450 lm
Correlated colour temperature	6500 K
Colour consistency in McAdam ellipses	≤6
Warranty (years)	2
Survival factor	0.9
Lifetime L70B50	50 000
Supply voltage range and voltage type	220-240 VAC
Frequency of the supply voltage	50/60Hz


Parameter	Value
Colour rendering index Ra	80
The lumen maintenance factor	96 %
Lamp's diameter	50
Beam angle	120 °
Lifespan	50000
Power Factor	0,5
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
Height	57 mm
Energy class	A+

Single packaging




Width	1560 mm
Height	30 mm
Length	30 mm
Weight	0,02 kg
	1

Bulk packaging



Number of pieces/tape in meters pack zb	100 szt.
Width	530 mm
Height of collective packaging	145 mm
Length	270 mm
Weight	3 kg
Volume	0,020 m ³

Europallet



Number of pieces/tapes in meters euro pallet	4400
Quantity collective euro pallet	5200 szt.
Weight of a euro pallet	156 kg
Pallet height	1885 mm
Quantity in 1 layer	400 szt.
Number of layers	13