

LED line LITE

Code: 245497

EAN: 5901583245497

LEDOM BULKHEAD 12W 4000K 220-240V oval SMD5730



Technical data

Parameter	Value	Parameter	Value
Luminous efficacy	70 lm/W	LED quantity	28
Colour of the light	White	Lifespan	30000
Energy efficiency class 2019/2015	E	Power Factor	0,5
Luminous flux	840 lm	Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6	Colour consistency in McAdam ellipses	≤6
IP protection rating	IP54	Ambient temperature suitable for operation	-40÷45 °C
Warranty (years)	3	For indoor and outdoor use	YES
Survival factor	0.9	IEC protection class	II
Lifetime L70B50	50 000	Lamp's warm-up time to 60%	1
Frequency of the supply voltage	50/60Hz	Length	216 mm
Colour rendering index Ra	80	Width	143 mm
Colour	White	Height	79 mm
The lumen maintenance factor	96 %	Energy class	A+
Beam angle	120 °	Power	• 12 W
Material (cover)	polycarbonate	Voltage	• 220-240 V AC
Material (housing)	Polycarbonate	Correlated colour temperature	• 4000 K
LED type	5730		

LED line LITE

Code: 245497


EAN: 5901583245497

LEDOM BULKHEAD 12W 4000K 220-240V oval SMD5730


Dimensions

Light distribution

Additional product photos




Logistics data




Single packaging

Width	216 mm
Height	79 mm
Length	143 mm
Weight	0,23 kg
	1



Bulk packaging

Number of pieces/tape in meters pack zb	24 szt.
Width	530 mm mm
Height of collective packaging	275 mm
Length	455 mm mm
Weight	5,87 kg kg
Volume	0,066 m3 m3



Europallet

Number of pieces/tapes in meters euro pallet	576
Quantity collective euro pallet	336 szt.
Weight of a euro pallet	82,18 kg kg
Pallet height	1925 mm
Quantity in 1 layer	48 szt.
Number of layers	7

LED line LITE

Code: 245497

EAN: 5901583245497

**LEDOM BULKHEAD 12W 4000K 220-
240V oval SMD5730**

Example application