

LED line PRIME

Code: 200364

EAN: 5905378200364

LED line PRIME Floodlight 200W 4000K
28000lm 60°



Technical data

Parameter	Value
Luminous efficacy	140 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	28000 lm
Colour consistency in McAdam ellipses	≤6
IP protection rating	IP66
Warranty (years)	5
Survival factor	0.9
Lifetime L70B50	50 000
Wire length	1 050 mm
Weight	3,3 g
Mounting type	surface
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	70
The lumen maintenance factor	96 %
Beam angle	60 °
Material (cover)	tempered glass
Material (housing)	aluminum

Parameter	Value
LED type	SMD2835
LED quantity	360
Power Factor	0,9
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-40÷45 °C
For indoor and outdoor use	YES
IEC protection class	I
IK protection rating	08
Full box quantity	1 pc
Lamp's warm-up time to 60%	1
Length	412 mm
Width	360 mm
Height	54 mm
Power	• 200 W
Voltage	• 100-227 V AC
Correlated colour temperature	• 4000 K

LED line PRIME

Code: 200364


EAN: 5905378200364

LED line PRIME Floodlight 200W 4000K
28000lm 60°


Dimensions

Light distribution

Additional product photos




Logistics data




Single packaging

Width	412 mm
Height	54 mm mm
Length	360 mm mm
Weight	3,57 kg kg



Bulk packaging

Number of pieces/tape in meters pack zb	1 szt.
Width	450 mm mm
Height of collective packaging	80 mm
Length	420 mm mm
Weight	0 kg kg
Volume	0,015 m3 m3



Europallet

Number of pieces/tapes in meters euro pallet	60
Quantity collective euro pallet	48 szt.
Weight of a euro pallet	25 kg kg
Pallet height	1920 mm
Quantity in 1 layer	2 szt.
Number of layers	24

LED line PRIME

Code: 200364

EAN: 5905378200364

**LED line PRIME Floodlight 200W 4000K
28000lm 60°**

Example application