

LED line PRIME

Code: 200005

EAN: 5905378200005

LED line PRIME LED strip 480 COB 24V
2700K 11W 30m



Technical data

Parameter	Value	Parameter	Value
Luminous efficacy	100 lm/W	LED type	COB
Colour of the light	White	LED quantity	2400
Energy efficiency class 2019/2015	F	Compatible dimmer type	PWM
Colour consistency in MacAdam ellipses	≤3	Laminate (colour)	White
IP protection rating	IP20	Laminate (thickness)	2
Warranty (years)	5	LED quantity (lm)	480
Dimmable function	PWM	Cutting section	5
Survival factor	0.9	Type of adhesive tape	3M 300 LSE
Minimum purchase quantity	30	Colour consistency in MacAdam ellipses	≤3
Lifetime L70B50	50 000	Ambient temperature suitable for operation	-30 ÷ 45 °C
Wire length	200 mm	For indoor use	Inside
Wattage (lm)	11 W	Length	30000 mm
Luminous flux (lm)	1100	Width	8 mm
Current (lm)	0,46	Height	2 mm
Colour rendering index Ra	90	Power	• 11
Metres per roll	30 m	Voltage	• 24 V DC
The lumen maintenance factor	96 %	Correlated colour temperature	• 2700 K
Beam angle	180 °		

LED line PRIME

Code: 200005


EAN: 5905378200005

LED line PRIME LED strip 480 COB 24V
2700K 11W 30m


Dimensions

Light distribution

Additional product photos




Logistics data




Single packaging

Width	380 mm
Height	130 mm mm
Length	400 mm mm
Weight	0,71 kg
	30



Bulk packaging

Number of pieces/tape in meters pack zb	20 szt.
Width	450 mm
Height of collective packaging	290 mm
Length	350 mm
Weight	14,1 kg
Volume	0,045 m3



Europallet

Number of pieces/tapes in meters euro pallet	14400 m
Quantity collective euro pallet	480 szt.
Weight of a euro pallet	278,8
Pallet height	1740 mm
Quantity in 1 layer	80 szt.
Number of layers	6

LED line PRIME

Code: 200005

EAN: 5905378200005

**LED line PRIME LED strip 480 COB 24V
2700K 11W 30m**

Example application