

LED line PRIME


Code: 210264

EAN: 5905378210264

Waterproof fixture RANGER 60-80W  
4000K 14400lm 150cm PRIME



The 60-80W and 14 400 lm RANGER sealed housing is an excellent choice for applications requiring solid lighting. With 4,000K light colour, it provides neutral, pleasant glow. Thanks to IP66 tightness class and IK10 resistance, the product is resistant to water and impact. It is characterized by high energy efficiency (class C) and a power factor PF of 0.9.



Technical data

Parameter	Value
Luminous efficacy	180
Colour of the light	White
Energy efficiency class 2019/2015	C
Luminous flux	14400
Colour consistency in McAdam ellipses	≤6
Warranty (years)	5
IP protection rating	IP66
Survival factor	0.9
Lifetime L70B50	100 000 h
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	Grey
The lumen maintenance factor	96
Beam angle	120

Parameter	Value
Material (cover)	polycarbonate
Material (housing)	Polycarbonate
LED type	SMD2835
LED quantity	400
Power Factor	0,9
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-25÷45
IEC protection class	II
IK protection rating	10
Lamp's warm-up time to 60%	1 s
Correlated colour temperature	• 4000 K
Power	• 60-80 W

LED line PRIME

Code: 210264

EAN: 5905378210264

**Waterproof fixture RANGER 60-80W  
4000K 14400lm 150cm PRIME**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

---

LED line PRIME

Code: 210264

EAN: 5905378210264

**Waterproof fixture RANGER 60-80W  
4000K 14400lm 150cm PRIME**

---

**Example application**