

LED line PRIME żarówka LED GU10 10W 6500K 1400lm 170-250V



Manufacturer issues a 5-year warranty for this product.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Voltage range and voltage type



LED type



The structural design of this product ensures effective heat dissipation.



Beam angle



Lamp type



Lifespan

Parameter	Value
Luminous efficacy	140 lm/W
Power	10 W
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	1400 lm
Correlated colour temperature	6500 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	20
Warranty (years)	5
Survival factor	0.9
Lifetime L70B50	30 000
Material	Ceramic
Supply voltage range and voltage type	170-250 VAC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White

Parameter	Value
The lumen maintenance factor	96 %
Lamp's type	GU10
Lamp's diameter	50
Beam angle	120 °
Material (housing)	Ceramic
LED type	SMD2835
Lifespan	30000
Power Factor	0,5
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
For indoor use	Inside
Full box quantity	100 pc
Lamp's warm-up time to 60%	1
Height	55 mm
Master carton weight (kg)	7

Single packaging




Width	50 mm
Height	63 mm
Length	50 mm
Weight	0,06 kg
	1

Bulk packaging



Number of pieces/tape in meters pack zb	100 szt.
Width	575 mm
Height of collective packaging	155 mm
Length	280 mm
Weight	7 kg
Volume	0,024 m ³

Europallet



Quantity collective euro pallet	4800 szt.
Weight of a euro pallet	336 kg
Pallet height	1860 mm
Quantity in 1 layer	400 szt.
Number of layers	12