

LED line PRIME

Code: 204126

EAN: 5905378204126

LED line PRIME FUSION linear lamp
40W 4000K 5200lm 90*110° white



LED line luminaire PRIME FUSION 40W with colour temperature 4000K provides an impressive light stream of 5200 lumens. It is characterized by high energy efficiency of 130 lm/W and a power factor PF of 0.9. It offers a light distribution angle of 90° x 110°, providing optimal space illumination.



Technical data

Parameter	Value
Voltage	• 220-240 V AC
Sling length	200 cm
Luminous efficacy	130
Colour of the light	White
Energy efficiency class 2019/2015	C
Luminous flux	5200
Colour consistency in McAdam ellipses	≤6
Standby power	0
Warranty (years)	5
IP protection rating	IP20
Survival factor	0.9
Lifetime L70B50	50 000 h

Parameter	Value
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
The lumen maintenance factor	96
Power Factor	0,9
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
IEC protection class	I
IK protection rating	08
Lamp's warm-up time to 60%	1 s
Correlated colour temperature	• 4000 K
Power	• 40 W

LED line PRIME

Code: 204126


EAN: 5905378204126

**LED line PRIME FUSION linear lamp
40W 4000K 5200lm 90*110° white**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 204126

EAN: 5905378204126

**LED line PRIME FUSION linear lamp
40W 4000K 5200lm 90*110° white**

Example application