LED line PRIME

Code: 204126

EAN: 5905378204126

Linear luminaire FUSION 4000K 40W 5200lm 90*110° IP20 120cm white PRIME

LED line luminaire PRIME FUSION 40W with colour temperature 4000K provides an impressive light stream of 5200 lumens. It is characterized by high energy efficiency of 130 lm/W and a power factor PF of 0.9. It offers a light distribution angle of 90° x 110°, providing optimal space illumination.

5 WARRANTY | 7 WARRANTY | IP 20 | IK 08 | PF 0,9 | 220-240V AC

Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5/7*
Power	• 40 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	08
IEC protection class	I
Luminous efficacy	130
Luminous flux	5200
The lumen maintenance factor	96

Parameter	Value
Lifetime L70B50	50 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Sling length	200 cm
Standby power	0
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
Height	52

T: +48 29 764 77 00 export@ledline.pl **www.ledline.pl/en**

LED line PRIME | Code: 204126 | EAN: 5905378204126

Linear luminaire FUSION 4000K 40W 5200lm 90*110° IP20 120cm white PRIME

Technical drawing



Light distribution

Additional product photos



Logistics data



Single packaging

Width	1158 mm
Height	52 mm
Length	70 mm
Weight	1,82 kg



Bulk packaging

Quantity	12
Width	1260 mm
Height	260 mm
Length	260 mm
Volume	0,085 m3
Weight	22,09 kg
Comments	



Europallet

Quantity	288
Height	1260 mm
Quantity in layer	144
Number of layers	1
Bulk quantity	144
Weight	265,2 kg

LED line PRIME | Code: 204126 | EAN: 5905378204126

Linear luminaire FUSION 4000K 40W 5200lm 90*110° IP20 120cm white PRIME

Example application