


LED line® PHOTON 30W 6000K 80lm/w 220-240V AC PIR



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



Manufacturer issues a 3-year warranty for this product.



The structural design of this product ensures effective heat dissipation.



Voltage range and voltage type



Motion detection angle



Lifespan



Dimmable



This product is featured by a high degree of IP protection, which makes it suitable for a broader range of lighting applications and offers high safety of use.



Easy assembly without the need to disassemble the arm.



Beam angle



Ambient temperature suitable for operation



LED type




LED quantity

| Parameter | Value |
|--|------------------------|
| Luminous efficacy | 80 lm/W |
| Power | 30 W |
| Colour of the light | White |
| Wyniki tłumaczenia Functional description of the daylight sensor [LUX] | Min 5 lx - Max 2000 lx |
| Energy efficiency class 2019/2015 | F |
| Luminous flux | 2400 lm |
| Correlated colour temperature | 6000 K |
| Colour consistency in McAdam ellipses | ≤6 |
| IP protection rating | 65 |
| Warranty (years) | 3 |
| Survival factor | 0.9 |
| Lifetime L70B50 | 25 000 |
| Wire length | 2 000 mm |
| Rated power | 220-240V AC |
| Weight | 530 g |
| Mounting type | surface |

| Parameter | Value |
|--|----------------|
| Beam angle | 120 ° |
| Sensor type | PIR |
| Material (cover) | tempered glass |
| Material (housing) | aluminum |
| LED type | SMD2835 |
| LED quantity | 42 |
| Lifespan | 25000 |
| Power Factor | 0,9 |
| Number of on/off cycles | 18000 |
| Colour consistency in McAdam ellipses | ≤6 |
| Ambient temperature suitable for operation | -20÷45 °C |
| For indoor and outdoor use | YES |
| IEC protection class | I |
| IK protection rating | 06 |
| Lamp's warm-up time to 60% | 1 |
| Length | 147 mm |


| | | | |
|---------------------------------------|-------------|-------------------------------|--------|
| Supply voltage range and voltage type | 220-240 VAC | Width | 61 mm |
| Frequency of the supply voltage | 50/60Hz | Height | 208 mm |
| Colour rendering index Ra | 80 | Product weight with packaging | 605 g |
| Colour | Black | Energy class | A+ |
| The lumen maintenance factor | 96 % | | |

Luminous [cd/klm]




C0 - C180 C90 - C270

Single packaging




| | |
|--------|---------|
| Width | 147 mm |
| Height | 208 mm |
| Length | 61 mm |
| Weight | 0,55 kg |
| | 1 |

Bulk packaging



| | |
|---|----------|
| Number of pieces/tape in meters pack zb | 20 szt. |
| Width | 445 mm |
| Height of collective packaging | 330 mm |
| Length | 397 mm |
| Weight | 11,35 kg |
| | 0,058 |
| Volume | m3 |

Europallet



| | |
|--|----------|
| Number of pieces/tapes in meters euro pallet | 320 |
| Quantity collective euro pallet | 400 szt. |
| Weight of a euro pallet | 227 kg |
| Pallet height | 1650 mm |
| Quantity in 1 layer | 80 szt. |
| Number of layers | 5 |