

LED line PRIME

Code: 248139-II

EAN: 5905378201965

LED line PRIME LED Bulb MR11 3W
2700K 330lm 10-14V AC/DC 38°



product_card.label_technical_data

Parameter	Value	Parameter	Value
Luminous efficacy	110 lm/W	Beam angle	38 °
Colour of the light	White	Material (housing)	Ceramic
Energy efficiency class 2019/2015	F	LED type	SMD2835
Luminous flux	330 lm	Lifespan	30000
Colour consistency in McAdam ellipses	≤6	Power Factor	0,5
IP protection rating	IP20	Number of on/off cycles	50000
Warranty (years)	5	Colour consistency in McAdam ellipses	≤6
Survival factor	0.9	Ambient temperature suitable for operation	-5+40 °C
Lifetime L70B50	30 000	For indoor use	Inside
Material	Ceramic	Full box quantity	100 pc
Frequency of the supply voltage	50/60Hz	Lamp's warm-up time to 60%	1
Colour rendering index Ra	80	Height	35 mm
Colour	White	Power	• 3 W
The lumen maintenance factor	96 %	Voltage	• 10-14 V AC/DC
Lamp's type	MR11	Correlated colour temperature	• 2700 K
Lamp's diameter	35		

LED line PRIME

Code: 248139-II

EAN: 5905378201965

LED line PRIME LED Bulb MR11 3W
2700K 330lm 10-14V AC/DC 38°


product_card.label_dimensions

product_card.label_curve_light

product_card.label_product_gallery




product_card.label_logistic_data




Single packaging

Width	50 mm
Height	57 mm mm
Length	50 mm mm
Weight	0,03 kg kg
	1



Bulk packaging

Number of pieces/tape in meters pack zb	100 szt.
Width	420 mm mm
Height of collective packaging	115 mm
Length	205 mm mm
Weight	5 kg kg
Volume	0,009 m3 m3



Europallet

Quantity collective euro pallet	9600 szt.
Weight of a euro pallet	480 kg
Pallet height	1840 mm
Quantity in 1 layer	600 szt.
Number of layers	16

LED line PRIME

Code: 248139-II

EAN: 5905378201965

**LED line PRIME LED Bulb MR11 3W
2700K 330lm 10-14V AC/DC 38°**

Example application