

LED line LITE

Code: 477613

EAN: 5907777477613

Hermetic luminaire TRI-PROOF 4000K
40W 4800lm IP65 120cm gray LITE



LED line LITE TRI-PROOF 40W is an innovative solution with a length of 1250 mm and a colour temperature of 4000K. Thanks to the impact-resistant polycarbonate housing and increased IP65 protection, it provides excellent tightness and durability in difficult conditions. Light efficiency is 4800 lumens at 40W, which guarantees energy-efficient use.

3
WARRANTY

IP
65

IK
08

PF
0,9

185-265V
AC

MAX
-20+60°C

CE

Technical data

Parameter	Value	Parameter	Value
Energy efficiency class 2019/2015	E	Standby power	0
Warranty	3	Mounting type	surface
Power	• 40 W	Frequency of the supply voltage	50/60Hz
Voltage	• 185-265 V AC	CRI colour rendering index	80
Correlated colour temperature	• 4000 K	Beam angle	120
Colour of the light	White	LED type	2835
Colour rendering index Ra	80	LED quantity	144
IK protection rating	08	Lifespan	35 000 h
IEC protection class	II	Power Factor	0,9
Luminous efficacy	120	Number of on/off cycles	20000
Luminous flux	4800	Lamp's warm-up time to 60%	1
The lumen maintenance factor	96	Ambient temperature suitable for operation	-20÷40
Lifetime L70B50	35 000 h	Height	48
Survival factor	0.9	Colour	White
Colour consistency in McAdam ellipses	≤6	Material (housing)	Polycarbonate
ULOR	10 %	Material (cover)	Polycarbonate

LED line LITE


Code: 477613

EAN: 5907777477613


Hermetic luminaire TRI-PROOF 4000K

40W 4800lm IP65 120cm gray LITE

Technical drawing





Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	1250 mm
Height	48 mm
Length	82 mm
Weight	0,9 kg

Bulk packaging

Quantity	10
Width	270 mm
Height	190 mm
Length	1260 mm
Volume	0,064 m3
Weight	9,35 kg
Comments	

Europallet

Quantity	160
Height	1,6 m
Quantity in layer	160
Number of layers	1
Bulk quantity	16
Weight	175 kg

LED line LITE

Code: 477613

EAN: 5907777477613

**Hermetic luminaire TRI-PROOF 4000K
40W 4800lm IP65 120cm gray LITE**

Example application