

LED line PRIME

Code: 220621

EAN: 5905378220621

**Street luminaire TOLENO Icl 4000K  
100W 15000lm T2M1 IP66 Gray (RAL  
9007) CRI70 PRIME**



TOLENO is a two-chamber street luminaire made of high-pressure aluminum die-casting with a high IP66 tightness and IK09 mechanical impact resistance. Tool-free access, a knife switch, wide adjustment of the mounting bracket, and an integrated level speed up installation and service. The tempered glass cover, directional multi-lens matrices, high-efficiency diodes, and the ability to adjust the luminaire's power ensure optimal lighting parameters. The Zhaga interface and programmable DALI driver enable integration with control systems.



**Technical data**

Parameter	Value
Energy efficiency class 2019/2015	B
Warranty	5/7*
Power	• 100 W
Voltage	• 100-277 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	09
IEC protection class	I
Luminous efficacy	150
Luminous flux	15000
Lifetime L70B50	100 000 h

Parameter	Value
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	100000 h
L90B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	100000 h
Dimmable function	0-10
Frequency of the supply voltage	50/60Hz
Beam angle	T2M1
Power Factor	>0,95
Ambient temperature suitable for operation	-40 ÷ 45
For indoor use	Outside
Height	124 mm
Fixture's diameter	48-60 mm
Material (housing)	Aluminium
Material (cover)	Tempered glass
Lifetime L80B10	100 000


LED line PRIME

Code: 220621


EAN: 5905378220621

**Street luminaire TOLENO Icl 4000K  
100W 15000lm T2M1 IP66 Gray (RAL  
9007) CRI70 PRIME**

**Technical drawing**



**Light distribution**



**Additional product photos**



**Logistics data**



**Single packaging**

Width	530 mm
Height	120 mm
Length	265 mm
Weight	3,61 kg

**Bulk packaging**

Quantity	1
Width	530 mm
Height	120 mm
Length	265 mm

**Europallet**

Quantity	72
Height	1900 mm
Quantity in layer	
Number of layers	
Bulk quantity	72
Weight	310 kg

LED line PRIME

Code: 220621

EAN: 5905378220621

**Street luminaire TOLENO Icl 4000K  
100W 15000lm T2M1 IP66 Gray (RAL  
9007) CRI70 PRIME**

**Example application**

